



2310 E. Orangethorpe Ave, Anaheim, CA 92806

714-738-6194 / 714-446-0119 FAX


www.accrmfg.com

Series 1775-X Extractor Lever Product Specification

Part Number Code:

Injector / Ejector Series and Card Size	1775-X	PP	BA	SS	SilkScreen Option:
X = Card thickness in 32nds					SS = Silk Screen Required (per customer request/artwork)
1 = 1/32" Card Thickness (.031" REF)					Leave Blank = None Required
2 = 2/32" Card Thickness (.062" REF)					Finish Option:
3 = 3/32" Card Thickness (.093" REF)					BA = Black Anodize per Mil-A-8625, Type II, Class 2
4 = 4/32" Card Thickness (.125" REF)					BH = Black Hard Anodize per Mil-A-8625, Type III, Class 2
Hardware Option:					CC = Chem-Film Clear per MIL-C-5541, CL 3 (ROHS)
PP = One Assembly Pin Pre-Started, One Pin Shipped Loose					CG = Chem-Film Gold per MIL-C-5541, CL 1A
Blank = Two Loose Pins (Stainless 3/32" X 1/4") per Lever					RA = Red Anodize per Mil-A-8625, Type II, Class 2
					Other colors available on request.

Note: Pins and Latch Spring are Stainless Steel and Passivated. Lever and Latch are Made From 6061-T6 Aluminum



BOARD THICKNESS CHART:

Part #	Board Thickness	"W" Dim
1775-1	1/32 - .031	.048"
1775-2	2/32 - .062	.080"
1775-3	3/32 - .093	.110"
1775-4	4/32 - .125	.140"

**ACCR Products are 100% Made in the USA.

FEATURES:

- *High-Strength Lever Action Design Overcomes Extreme Insertion and Ejection Forces.
- *Actuates from a Simple "U" Channel Form.
- *Available with Conductive Finish.
- *Clearance Chamfer not Required on Circuit Board.
- *Narrow Profile to Minimize Interference.
- *Positive Locking Prevents PCB from Backing Out.