

Series 3220 - Product Specification



Part Number Code:

ACCR Series	3220	MVW	BA	-	X.XX	H	L	R	Option R = Locknut for retaining the screw
Hardware Option:									
1st Position Blank = 3/32" Hex Socket - Std									
M = Metric 2.5 Hex Socket Head On Screw									
V = Visual Lock Indicator (Add .20" To Screw Length)									
W = Lock And Flat Washer (Add .06" To Screw Length)									
Finish Option:									
BA = Black Anodize per Mil-A-8625, Type II, Class 2									
BH = Black Hard Anodize per Mil-A-8625, Type III, Class 2									
CC = Chem-Film Clear per Mil-C-5541 (ROHS)									
CG = Chem-Film Gold per Mil-C-5541									
EN = Electroless Nickel per Mil-C-26074									
BL = Black Hard Anodize with Dry Film Lube per Mil-L46010									
RA = Red Anodize per Mil-A-8625, Type II, Class 2									
	Mounting Options:								
	E = Extra mounting hole								
	H = C'bore .156" Dia. X .200" Deep X .068/.073" Dia. Hole Thru, CSK 100 degree X .140" Dia.								
	T0 = 0-80 Tapped Thru Holes								
	T2 = 2-56 Tapped Thru Holes								
	TM2 = Metric 2 Tapped Thru Holes								
	TM2.5 = Metric 2.5 Tapped Thru Holes								
	P = Indexing Pins .062 x .050" (two positions only)								
	Assembly Length in decimal inches:								
	Standard lengths = 2.80, 3.80 and 4.80								
	Other lengths or specifications on request.								

