



DIP14

LITTLE FOOT® (continued)

Part Number	V _{DS} (V)	Maximum Ratings				Configuration
		V _{GS} = ±10 V	V _{GS} = ±4.5 V	V _{GS} = ±2.7 V	I _D (A)	
Complementary LITTLE FOOT® Devices (SOIC 8)						
Si9529DY	20		0.03	0.04	6	N-Channel
	-12		0.05	0.074	5	P-Channel
Si9928DY	20		0.05	0.08	±5	N-Channel
	-20		0.11	0.19	±3.4	P-Channel
Si9942DY	20	0.125	0.25		±2.5	N-Channel
	20	0.2	0.35		±3	P-Channel
Si9958DY	20	0.10	0.15		±3.5	N-Channel
	-20	0.10	0.19		±3.5	P-Channel
Si9952DY	25	0.1	0.15		3.5	N-Channel
	-25	0.25	0.4		2.3	P-Channel
Si4539DY	30	0.037	0.055		±5.8	N-Channel
	-30	0.053	0.095		±4.9	P-Channel
Si4558DY	30	0.04	0.06		6	N-Channel
	-30	0.04	0.07		6	P-Channel
Si4949EY	60	0.055	0.075		4.5	N-Channel
	-30	0.053	0.095		5.1	P-Channel
Si9939DY	30	0.05	0.08		±3.5	N-Channel
	-30	0.1	0.16		±3.5	P-Channel
Si4532DY	30	0.065	0.095		±3.9	N-Channel
	-30	0.085	0.190		±2.5	P-Channel
N-Channel LITTLE FOOT® Devices (TSOP6)						
Si3442DV	20		0.07	0.095	4	Single
Si3454DV	30	0.065	0.095		4.2	Single
P-Channel LITTLE FOOT® Devices (TSOP6)						
Si3441DV	-20		0.1	0.135	3.3	Single
Si3455DV	-30	0.1	0.19		3.5	Single